



# Thermocouple feedthrough, type K

PFEIFFER 




Illustration only

## Thermocouple feedthrough, type K, 5 pairs, with MS plug, DN 16 CF

- 5 Thermocouple pairs type K: Chromel (+) /Alumel (-)
- Thermocouple type E, J on request
- Incl. MS plug as per MIL-C-5015, atmosphere side (-65 to 125 °C)

## Dimensions



<b>Technical Data</b>	<b>Thermocouple feedthrough, type K, 5 pairs, with MS plug, DN 16 CF</b>
Materials in contact with media	Flange: Stainless steel
Temperature range (vacuum side)	100 – 300 °C
Tightness	1 · 10 <sup>-11</sup> Pa m <sup>3</sup> /s   7.5 · 10 <sup>-11</sup> Torr l/s   1 · 10 <sup>-10</sup> mbar l/s
Heat up and cool down rate	≤20 K/min
Connection flange	DN 16 CF
Pressure range	1 · 10 <sup>-11</sup> hPa – to ambient pressure

<b>Order number</b>	<b>Thermocouple feedthrough, type K, 5 pairs, with MS plug, DN 16 CF</b>
Thermocouple feedthrough, type K, 5 pairs, with MS plug, DN 16 CF	420XTK016-5-S



Errors and/or changes excepted. - 5/14/2025

Are you looking for an optimum vacuum solution?

Talk to us:

**Pfeiffer Vacuum Components & Solutions GmbH Germany**

**T +49 551 99963-0**

**info-cs@pfeiffer-vacuum.com**

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>

Follow Us On Social Media

#pfeiffervacuum



[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

**PFEIFFER** 