

**Corrugated hose,
braided; stainless steel,
DN 25 ISO-KF, length
1000 mm**

PFEIFFER 

Corrugated hose, braided




Illustration only

Corrugated hose, braided; stainless steel, DN 25 ISO-KF, length 1000 mm

- Custom lengths on request

Dimensions



Technical Data	Corrugated hose, braided; stainless steel, DN 25 ISO-KF, length 1000 mm
Temperature range	196 – 300 °C
Bending radius, frequent movement	180 mm 7.09 inch
Bending radius, one-time movement	64 mm 2.52 inch
Connection flange	DN 25 ISO-KF
Pressure range	$1 \cdot 10^{-8}$ hPa – $5 \cdot 10^2$ hPa over pressure
Material	Stainless steel: Flange and braiding 1.4301/304; Bellows 316L
Temperature range max.	300 °C 572 °F 573.15 K
Temperature range min.	196 °C 320.8 °F 77.15 K

Order number	Corrugated hose, braided; stainless steel, DN 25 ISO-KF, length 1000 mm
Corrugated hose, braided; stainless steel, DN 25 ISO-KF, length 1000 mm	120SWU025-1000



Errors and/or changes excepted. - 5/14/2025

Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum Components & Solutions GmbH Germany
T +49 551 99963-0
info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 