




ISO-K-Blank flange for ports, stainless steel 304/1.4301, DN 100 ISO- K



ISO-K-Blank flange for ports



ISO-K-Blank flange for ports, stainless steel 304/1.4301, DN 100 ISO-K

Technical Data	ISO-K-Blank flange for ports, stainless steel 304/1.4301, DN 100 ISO-K
Materials in contact with media	Stainless steel 1.4301 (AISI 304)
O-ring material	FKM
Temperature range	-196 – 300 °C
Connection flange	DN 100 ISO-K
Pressure range	< 1E-7 hPa – 5E2 hPa over pressure (elastomer seal); 1E-9 hPa – 5E2 hPa over pressure (metal seal)
Temperature range max.	300 °C 572 °F 573.15 K
Temperature range min.	-196 °C -320.8 °F 77.15 K

Order number	ISO-K-Blank flange for ports, stainless steel 304/1.4301, DN 100 ISO-K
ISO-K-Blank flange for ports, stainless steel 304/1.4301, DN 100 ISO-K	820KB100



Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum Components & Solutions GmbH Germany
T +49 551 99963-0
info-cs@pfeiffer-vacuum.com
Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 11/1/2024

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

