



# CF blank flange for ports



## CF-blank flange for ports, stainless steel 304L, DN 130 CF

- With copper gasket and screws

Technical Data	CF-blank flange for ports, stainless steel 304L, DN 130 CF
Materials in contact with media	Stainless steel (AISI 304L)
Temperature range	-196 – 300 °C
Connection flange	DN 130 CF
Pressure range	<1E-12 hPa – to ambient pressur · 10
Temperature range max.	300 °C   572 °F   573.15 K
Temperature range min.	-196 °C   -320.8 °F   77.15 K

Order number	CF-blank flange for ports, stainless steel 304L, DN 130 CF
CF-blank flange for ports, stainless steel 304L, DN 130 CF	820KBC130



Are you looking for an optimum vacuum solution?  
 Talk to us:  
**Pfeiffer Vacuum Components & Solutions GmbH Germany**  
 T +49 551 99963-0  
**info-cs@pfeiffer-vacuum.com**

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Follow Us On Social Media  
 #pfeiffervacuum



[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)



Errors and/or changes excepted. - 11/1/2024