

Copper gasket

PFEIFFER 




Illustration only

Copper gasket, vacuum-annealed, DN 40 CF

- Soft annealed under vacuum
- Particularly well suited for viewports
- For single use only

Dimensions



Technical Data

Technical Data	Copper gasket, vacuum-annealed, DN 40 CF
Materials in contact with media	OFHC Copper (Oxygen Free), vacuum-annealed
Package	5 Pieces
Temperature range	196 – 200 °C
Connection flange	DN 40 CF
Pressure range	$1 \cdot 10^{-13}$ hPa – to ambient pressure
Temperature range max.	200 °C 392 °F 473.15 K
Temperature range min.	196 °C 320.8 °F 77.15 K

Order number

Order number	Copper gasket, vacuum-annealed, DN 40 CF
Copper gasket, vacuum-annealed, DN 40 CF	490DFL040-G-S5



Errors and/or changes excepted. - 5/14/2025

Are you looking for an optimum vacuum solution?

Talk to us:

Pfeiffer Vacuum Components & Solutions GmbH Germany

T +49 551 99963-0

info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>

Follow Us On Social Media

#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 